



P/N 6920HKR (painted) & 6920-1HKR (ceramic coated) COMPETITION HEADERS

Late 69-70 Falcon, Farilane, Torino, Ranchero, Cyclone & Montego (351C)
Late 69-70 Mustang / Cougar (351C)

NOTE: Fits 4V heads only.

NOTE: Will fit manual and automatic transmissions on the floor only.

NOTE: Installation requires power steering bracket 10961HKR.

Thank you for making HOOKER HEADERS your choice in a high-performance exhaust system. Extensive dyno/track testing has enabled HOOKER to offer the most advanced design in exhaust systems. The installation, while not complex, will take a certain amount of time. However, the additional horsepower and improved performance will more than justify your efforts. Proper installation and maintenance will ensure long life and maximum performance from your hooker exhaust system.

WARNING! Breaking in an engine with ceramic-coated headers WILL result in damage to the coating and will VOID all warranties. Ceramic-coated headers require several heat cycles to fully cure before they will withstand extreme heat. HOOKER recommends using a cast-iron exhaust manifold or an old header to break in new engines to avoid coating damage.

BEFORE STARTING

Your vehicle must be raised a minimum of 36 inches. A floor hoist is ideal. If no hoist is available, we strongly urge the use of axle stands as a safety measure. **CAUTION! YOUR CAR SHOULD NOT BE SUPPORTED ON A BUMPER JACK.**

INSTALLATION PROCEDURE – PLEASE READ CAREFULLY

LEFT SIDE:

1. Disconnect the battery cable to prevent damage to the electrical system.
2. Unbolt the headpipes from the exhaust manifolds and push aside.
3. Remove the spark plugs, exhaust manifold, clutch linkage, and cross shaft. If your vehicle is equipped with power steering, unbolt the power steering ram from the frame.

NOTE: The front bolts are easier to install if the oil filter is removed.

4. Starting from below, work the header up through the chassis and start the front bolt.
5. With the header loose, reinstall the clutch linkage cross shaft.
6. Remove the front bolt, place the gasket into position, and start all bolts.
7. Tighten all bolts evenly. Replace spark plugs.
8. Replace clutch linkage and oil filter (if removed).

RIGHT SIDE:

1. Remove the exhaust manifold and unbolt the idler arm from the frame.
2. Starting from below, work the header up through the chassis into position.
3. Place the gasket in position and start all bolts.
4. Tighten all bolts evenly. Reinstall the idler arm to the frame.
5. To connect the collectors to the stock headpipes, bolt the purchased reducers (with gaskets) to the collectors.
6. Connect the battery, start the engine and check for leaks. Be sure that all brake lines, fuel lines, and electrical wires have sufficient clearance.
7. When finished, give your vehicle a test drive, checking carefully for any new noises. After several days of driving, retighten all bolts.

Any questions? Please contact Technical Service: 1-866-GOHOLLEY or 270-781-9741. For online help, please refer to the website: www.holley.com.

LIMITATION OF LIABILITY – DISCLAIMER:

The regulation of emissions production, noise levels, and safety standards is undertaken by the federal government, each of the fifty state legislatures, and by many local municipalities, towns, and counties.

HOOKER makes no warranties of merchantability, of fitness for particular purpose, or that its products are approved for general use, or that its products are approved for general use, or that its products comply with laws, regulations, or ordinances in the state where they may be sold to the ultimate purchaser, the consumer.

Unless expressly stated to the contrary in the catalog, instruction sheet; or price list, the entire risk as to the conformity of any company product in any such state and as to repair should the product prove to be defective or non-conforming, is on the retail purchaser, the buyer, the ultimate consumer, of such product and it is not upon the seller, distributor, or manufacturer.

In this connection, the retail purchaser, the buyer, the ultimate consumer assumes the burden of the entire cost of any and all necessary service, alterations, or repair.

THE FOREGOING STATEMENT LIMITS THE LIABILITY OF THE MANUFACTURER.

California vehicle code, sections 27156 AND 38391, prohibits the advertising, offering for sale, or installation of any device, which modifies a vehicle's emission control system, unless exempted, unless otherwise noted. HOOKER Headers have not received an exemption from these code sections and are to legal for sale or use in California on vehicles originally equipped with catalytic converters, it is illegal, except for racing vehicles, which may never be driven upon a highway. To remove or otherwise render inoperative any emission control device on the regulated motor vehicles – check catalog listings to ensure proper application in the other 49 states, unless otherwise noted, HOOKER Headers are not legal for pollution-controlled motor vehicles, except for racing vehicles, which may never be used upon a highway and are not intended or applicable for highway use.

6920HKR

Date: 10-28-25